

CERTIFICATE OF CONFORMITY

129/24

Issuer's name: Issuer's address: KAVALIERGLASS, a.s. Křížová 1018/6, Prague 5 Production plant: Sklářská 359, 285 06 Sázava, Czech Republic

Object of the declaration: GLASS TUBES; RODS; CAPILLARIES



Material:Borosilicate glass SIMAX®, glass with high thermal and chemical resistanceCountry of origin:Czech RepublicPurpose of use:Application in technical, pharmaceutical, laboratory or food industry

The object of the certificate described above is in conformity with the requirements of the following standards and regulations:

Glass characteristics:

- ISO 3585 Borosilicate glass 3.3 Properties
 - Chemical durability (art. 4.1, 4.2, 4.3, 4.4)
 - Physical properties (art. 5.1, 5.2, 5.3, 5.4, 5.5, 5.6)
- Glass containers for pharmaceutical use
 - Eur. Ph 10th Edition 3.2.1 Glass Type I.
 - USP <660> Glass Type I.

Supporting data:

TEST / European Pharmacopoeia 10, Art. 3.2.1	UNIT	LIMIT	RESULT
Hydrolytic resistance - inner surfaces, test A	ml 0,01 mol/l HCl/100ml of leachate	max 0,40	0,04
Hydrolytic resistance - glass grains, test B	mol 0,02/I HCl/g max 0,1		0,038
Arsenic content	mg As/g	mg As/g max 0,1	

FOOD CONTACT:

<u>Commission Regulation (EU) No. 2023/2006</u>
Good manufacturing practice for materials and articles intended to come into contact with food

• Regulation EC No 1935/2004 of 27 October 2004

Directive on materials and articles intended to come into contact with food and repealing Directives 80/590/EEC and 89/109/EEC

• <u>Regulation of Czech Health Ministry Decree No. 38/2001 Coll.</u> Directive on articles intended to come into contact with foodstuffs

Directive 84/500EEC of 15 October 1984

Directive on the approximation of the laws of the Member States relating to ceramic articles intended to come into contact with foodstuffs.

• ISO 7086-1:2000 Glass hollowware in contact with food Release of lead and cadmium – Part 1: Test method

• <u>ISO 7086-2:2000 Glass hollowware in contact with food</u> Release of lead and cadmium – Part 2: Permissible limits

• <u>ISO 719:2000 Glass - Hydrolytic resistance of glass grains at 98 °C</u> Method of test and classification

• <u>ASTM E438 Standard Specification for Glasses in Laboratory Apparatus</u> Classification, chemical requirements of the glass

No heavy metals (lead, cadmium, mercury and hexavalent chromium):

- Regulation (EC) No. 987/2008 of 8 October 2008 amending Regulation (EC) No. 1907/2006 REACH as regards Annexes IV and V – glass was exempted from the obligation to register. The object of declaration does not contain any substances from the REACH – Candidate list of SVHC.
- Directive 2011/65/EC (RoHS II), amended by 2015/863/EC, on the restriction of the use of certain hazardous substances in electrical and electronic equipment, Annex II - extension of limitation regarding 4 additional substances.

Chemical characteristics (acc. to Regulation No 1907/2006/EC):

Composition:	CAS No.	EINECS No.	Component:	Concentration /Percent:
	65997-17-3	266-046-0	Glass, oxide, chemicals	100%

Chemical stability: Stable

• Chemical characteristics of borosilicate glass (approximate values) ASTM E438

Component	Content (percentage by weight)		
SiO ₂	80,3%		
B ₂ O ₃	13,0%		
Al ₂ O ₃	2,4%		
Na ₂ O + K ₂ O	4,3%		

Additional information:

These products are made of borosilicate glass, which does not harm the human health. Its characteristics are constantly tested and comply fully with the standard ISO 3585 Borosilicate glass 3.3 – Properties.

The producer declares that the products are safe when used in usual and proper way.

The producer has installed the Quality Assurance System according to ISO 9001 and thus guarantees that all products delivered to the market are in full conformity with the technical documentation and with all fundamental requirements to such products. Certificate No. 3258 100 23 52 0132 issued by TÜV CERT, Certification Body at TÜV NORD CERT GmbH.

The certificate is issued for the customer:

.....

Sázava, 29. 01. 2024

Place and date of issue

Krizová 1018/6 150 00 Praha 5 Ing. Kristýna Machová Zech Republic Project Quality Engineer -61.